

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600254
- **Trade name:** 1-K Anti-Rust Primer E-COLL
- **Article number:** 4317784305495
- **UFI:** MU0R-S4AG-SC01-9C3R
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
EDE Platz 1
D-42389 Wuppertal
Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07 GHS09

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

acetone
n-butyl acetate
butan-1-ol
propan-2-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700). May produce an allergic reaction.
Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

*** SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 2)

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220 ⚠ Acute Tox. 2, H330 ⚠ Press. Gas (Comp.), H280	30-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	20-30%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	10-20%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-10%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H332; STOT SE 3, H335	1-10%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-10%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	1-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-10%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	0.978%

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 3)

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Personal protection for the First Aider.
Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air.
Seek medical treatment in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.
Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.
Mouth respiratory protective device.

Additional information

Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

EU
(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 4)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Do not allow product to reach sewage system or any water course.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Open and handle receptacle with care.
Use only in well ventilated areas.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from oxidising agents.

Further information about storage conditions:

Keep container tightly sealed.
Protect from heat and direct sunlight.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 5)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection**· 8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 115-10-6 dimethyl etherIOELV Long-term value: 1920 mg/m³, 1000 ppm**CAS: 67-64-1 acetone**IOELV Long-term value: 1210 mg/m³, 500 ppm**CAS: 123-86-4 n-butyl acetate**IOELV Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm**CAS: 1330-20-7 xylene**IOELV Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin**CAS: 100-41-4 ethylbenzene**IOELV Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Keep away from foodstuffs, beverages and feed.

· Respiratory protection:

Not necessary if room is well-ventilated.
Use suitable respiratory protective device in case of insufficient ventilation.
Self-contained respiratory protective device.

· Hand protection

Protective gloves

· Material of gloves

Butyl rubber, BR
Recommended thickness of the material: ≥ 0.4 mm

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 6)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles

· Body protection: Protective work clothing*** SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

- **Colour:** Grey
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Not applicable, as aerosol.
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 1.2 Vol %
- **Upper:** 18.6 Vol %
- **Flash point:** -41 °C
- **Auto-ignition temperature:** Product is not selfigniting.
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Kinematic: 23 °C - 4 mm (ISO 2431)**
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 4,000 hPa
- **Density and/or relative density**
- **Density at 20 °C:** 0.83 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.

· 9.2 Other information

- **Appearance:**
- **Form:** Aerosol
- **Important information on protection of health and environment, and on safety.**
- **Ignition temperature:** 235 °C
- **Explosive properties:** Not determined.
- **Solvent separation test:**
- **VOC (EC) %** 85.10 %

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 7)

- **VOC (EC) g/l**
- **Solids content:** 16.1 %
- **Change in condition**
- **Softening point/range**
- **Oxidising properties** Not determined.
- **Evaporation rate** Not applicable.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols**
Extremely flammable aerosol. Pressurised container: May burst if heated.

- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 8)

· LD/LC50 values relevant for classification:		
CAS: 115-10-6 dimethyl ether		
Inhalative	LC50/4h	308 ppm (rat)
CAS: 67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/m ³ (rat)
CAS: 123-86-4 n-butyl acetate		
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	>21 ppm (rat)
CAS: 7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rat)
Inhalative	LC50/4h	>10.2 ppm (rat)
CAS: 1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 67-63-0 propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4h	30 ppm (rat)
CAS: 71-36-3 butan-1-ol		
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4h	8,000 ppm (rat)
CAS: 100-41-4 ethylbenzene		
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
CAS: 1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Oral	LD50	11,400 mg/kg (rat)
Dermal	LD50	22,800 mg/kg (rabbit) (GESTIS)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 9)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****CAS: 67-64-1 acetone**

LC50 (96h)	5,000 mg/L (Lepomis macrochirus)
LC50/48h	8,800 mg/l (Daphnia magna)
NOEC	430 mg/l (algae)
NOEC/16h	1,700 mg/l (Pseudomonas putida)
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)
96h LC50	5,540 mg/l (Oncorhynchus mykiss)

CAS: 123-86-4 n-butyl acetate

LC50 (96h)	18 mg/L (Pimephales promelas)
EC50 (48h)	44 mg/L (Daphnia magna)
EC50/24h	73 mg/l (Daphnia magna)
EC50/72h	647.7 mg/l (S)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 10)

- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**
- **European waste catalogue**
16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **14.4 Packing group**
- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **Special marking (ADR):** Symbol (fish and tree)

- **14.6 Special precautions for user** Warning: Gases.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 11)

- **Hazard identification number (Kemler code):** -
 - **EMS Number:** F-D,S-U

 - **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

 - **Transport/Additional information:**
-
- **ADR**
 - **Limited quantities (LQ)** 1L
 - **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

 - **Transport category** 2
 - **Tunnel restriction code** D
-
- **IMDG**
 - **Limited quantities (LQ)** 1L
 - **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity

 - **UN "Model Regulation":** UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I Methanol**

 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

 - **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
 - **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**
- None of the ingredients is listed.

- **Exposure scenario(s)**
Exposure scenario(s) of ingredients (if present) are available on request at:
sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.02.2021

Version number 310

Revision: 01.02.2021

Trade name: 1-K Anti-Rust Primer E-COLL

(Contd. of page 12)

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH205 Contains epoxy constituents. May produce an allergic reaction.

• **Department issuing SDS:** Product safety department

• **Contact:** sdb@ede.de

• **Date of previous version:** 01.02.2021

• **Version number of previous version:** 309

• **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• *** Data compared to the previous version altered.**