

Page 1/11

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600273

- · Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL
- · Article number: 4317784662970, 4317784662987
- · UFI: 7PMU-9R0S-J905-0PG7
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- · Application of the substance / the mixture Metal working fluid

\cdot 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms Void
- · Signal word Void

• **Hazard statements** H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.



Printing date 18.07.2023

Safety data sheet

according to 1907/2006/EC, Article 31

Version number 301

Revision: 18.07.2023

(Contd. of page 1)

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH208 Contains 2-n-butyl-benzo[d]isothiazol-3-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-56-9 EINECS: 265-159-2 Index number: 649-469-00-9	Distillates (petroleum), solvent-dewaxedlight paraffinic	10-<25%
CAS: 68920-66-1 Reg.nr.: 01-2119489407-26	Fettalkohol, ethoxyliert Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-10%
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-0000	2-(2-butoxyethoxy)ethanol	<1.25%
CAS: 90-43-7 EINECS: 201-993-5 Index number: 604-020-00-6	biphenyl-2-ol Aquatic Acute 1, H400 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	0.1-<1%
CAS: 4299-07-4 ELINCS: 420-590-7 Index number: 606-079-00-3	2-n-butyl-benzo[d]isothiazol-3-one ♦ Skin Corr. 1B, H314 ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ♦ Skin Sens. 1, H317	0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

(Contd. of page 2)

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

Seek medical treatment in case of complaints.

• After skin contact: If skin irritation continues, consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to section 13.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

(Contd. on page 4)

EU -





according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

(Contd. of page 3)

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Provide floor trough without outlet. Store in a cool and dry place.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

CAS: 112-34-5 2-(2-butoxyethoxy)ethavjet	 Ingredients with limit values that require monitoring at the workplace: 				
Imp-term value: 67.5 mg/m³, 10 pm ONELs CAS: 68920-66-1 Fettalkohol, ethosystem Dermal DNEL (worker) 2,080 mg/kg bw/day (professional use) Inhalative Long term value for emploves 294 mg/m³ (professional use) CAS: 112-34-5 2-(2-butoxyethoxy)=thanor 294 mg/m³ (professional use) Oral DNEL (populution) 1.25 mg/kg bw/day (cus) Dermal DNEL (populution) 20 mg/kg bw/day (cus) Dermal DNEL (populution) 10 mg/kg bw/day (cus) Dermal DNEL (population) 34 mg/m³ (cus) Inhalative DNEL (worker) 67.5 mg/m³ (professional use) DNEL (worker) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) PNEC-Autic compartment Water 0.1 mg/L (Sea Water) PNEC-Swage treatment plant 200 mg/L (S)	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol				
• DNELs CAS: 68920-66-1 Fettalkohol, ethoxyliert Dermal DNEL (worker) 2,080 mg/kg bw/day (professional use) Inhalative Long term value for employees 294 mg/m³ (professional use) CAS: 112-34-5 2-(2-butoxyethoxy)ethanol 20 mg/kg bw/day (cus) Oral DNEL (populution) 1.25 mg/kg bw/day (cus) Dermal DNEL (worker) 20 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees 0NEL (population) 10 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) • PNECs CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)					
CAS: 6892∪-66-1 Fettalkohol, ethoxyliert Dermal DNEL (worker) 2,080 mg/kg bw/day (professional use) Inhalative Long term value for employees 294 mg/m³ (professional use) CAS: 112-34-5 2-(2-butoxyethoxy)ethanol Oral DNEL (populution) 1.25 mg/kg bw/day (cus) Dermal DNEL (worker) 20 mg/kg bw/day (professional use) Dermal DNEL (worker) 20 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees DNEL (population) 10 mg/kg bw/day (cus) 0NEL (worker) 34 mg/m³ (cus) 67.5 mg/m³ (professional use) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) • PNECs V PNEC-Aquatic compartment Water PNEC-Sewage treatment plant 0.1 mg/L (Sea Water)	Long-term value: 67.5 mg/m ³ , 10 ppm				
Dermal Inhalative DNEL (worker) 2,080 mg/kg bw/day (professional use) 294 mg/m³ (professional use) 294 mg/m³ (professional use) CAS: 112-34-5 2-(2-butoxyethoxy)=than 1.25 mg/kg bw/day (cus) Oral DNEL (populution) 1.25 mg/kg bw/day (professional use) Dermal DNEL (population) 20 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees 34 mg/m³ (cus) 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (worker) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) PNEC s 20.00 mg/L (Sea Water) PNEC-Sewage treatment plant 0.1 mg/L (Sea Water)	· DNELs				
Inhalative Long term value for employees 294 mg/m³ (professional use) CAS: 112-34-5 2-(2-butoxyethoxy)=thander 1.25 mg/kg bw/day (cus) Oral DNEL (populution) 1.25 mg/kg bw/day (professional use) Dermal DNEL (worker) 20 mg/kg bw/day (cus) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees JNEL (worker) 34 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) PNEC-Aquitic compartment Water 0.1 mg/L (Sea Water) PNEC-Sevage treatment plant 200 mg/L (S)	CAS: 6892	20-66-1 Fettalkohol, etho	xylier	t	
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol Oral DNEL (populution) 1.25 mg/kg bw/day (cus) Dermal DNEL (worker) 20 mg/kg bw/day (professional use) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees 34 mg/m³ (cus) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) ONEL (population) 34 mg/m³ (cus) PNECs 20 NEL (population) 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)	Dermal	DNEL (worker)		2,080 mg/kg bw/day (professional use)	
Oral DNEL (populution) 1.25 mg/kg bw/day (cus) Dermal DNEL (worker) 20 mg/kg bw/day (professional use) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for emplyees 34 mg/m³ (cus) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) PNECs 34 mg/m³ (cus) PNEC-Aquatic compartment Water PNEC-Sewage treatment plant 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)	Inhalative	ve Long term value for employees		294 mg/m ³ (professional use)	
Dermal DNEL (worker) 20 mg/kg bw/day (professional use) DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees 34 mg/m³ (cus) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) ONEL (population) 34 mg/m³ (cus) PNECs CAS: 112-34-52-(2-butoxyethoxy)=tharus PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Swage treatment plant 200 mg/L (S)	CAS: 112-	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol			
DNEL (population) 10 mg/kg bw/day (cus) Inhalative Long term value for employees 34 mg/m³ (cus) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) DNEL (population) 34 mg/m³ (cus) ONEL (population) 34 mg/m³ (cus) PNECs CAS: 112-34-52-(2-butoxyethoxy)=tharrow PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Servage treatment plant 200 mg/L (S)	Oral	DNEL (populution)		1.25 mg/kg bw/day (cus)	
Inhalative Long term value for emplyees 34 mg/m³ (cus) 67.5 mg/m³ (professional use) 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) • PNECs CAS: 112-34-5 2-(2-butoxyethoxy)=thand PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sevage treatment plant 200 mg/L (S)	Dermal	DNEL (worker)		20 mg/kg bw/day (professional use)	
Image: Section 1 67.5 mg/m³ (professional use) DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) • PNECs CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)		DNEL (population)		10 mg/kg bw/day (cus)	
DNEL (worker) 67.5 mg/m³ (professional use) DNEL (population) 34 mg/m³ (cus) • PNECs CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)	Inhalative	ve Long term value for employees		34 mg/m³ (cus)	
DNEL (population) 34 mg/m³ (cus) • PNECs CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)				67.5 mg/m³ (professional use)	
• PNECs CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water) PNEC-Sewage treatment plant 200 mg/L (S)		DNEL (worker)		67.5 mg/m ³ (professional use)	
CAS: 112-34-5 2-(2-butoxyethoxy)ethanolPNEC-Aquatic compartment Water0.1 mg/L (Sea Water)PNEC-Sewage treatment plant200 mg/L (S)		DNEL (population)		34 mg/m³ (cus)	
PNEC-Aquatic compartment Water0.1 mg/L (Sea Water)PNEC-Sewage treatment plant200 mg/L (S)	· PNECs				
PNEC-Sewage treatment plant 200 mg/L (S)	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol				
	PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water)				
	PNEC-Sewage treatment plant 200 mg/L (S)			ng/L (S)	
(Contd. on page 5)				(Contd. on page 5)	

- EU -



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

(Contd. of page 4)

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

 General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Hand protection



Protective gloves

Only use chemical-protective gloves with CE-labelling of category III.

Material of gloves

Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Recommendation: safety glasses with side protection shield
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Fluid · Colour: Light brown · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling Undetermined. range · Flammability Not applicable. · Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable.





Page 6/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

	(Contd. of page
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	41 mm²/s
Kinematic: 23 °C - 4 mm (ISO 2431)	
Dynamic at 20 °C:	40 mPas
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.97 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Drip point:	
Oxidising properties	Not determined.
Evaporation rate	Not determined.
	Not determined.
Information with regard to physical hazard	
classes	
Example a factor of	Void
Explosives	
Explosives Flammable gases	Void
	Void Void
Flammable gases	
Flammable gases Aerosols Oxidising gases	Void
Flammable gases Aerosols	Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure	Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids	Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures	Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids	Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void Void Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable	Void Void Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Void Void Void Void Void Void
Flammable gases Aerosols Oxidising gases Gases under pressure Flammable liquids Flammable solids Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void Void Void Void



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

(Contd. of page 6)

Page 7/11

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxedlight paraffinic			
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
CAS: 68920-66-1 Fettalkohol, ethoxyliert			
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/6h	>100 mg/m³ (rat)	
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol			
Oral	LD50	4,900 mg/kg (rat)	
Dermal	LD50	4,900 mg/kg (rabbit)	
CAS: 90-43-7 biphenyl-2-ol			
Oral	LD50	2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

(Contd. of page 7)

Page 8/11

• Reproductive toxicity Based on available data, the classification criteria are not met.

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- \cdot 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

/iqualio ii						
CAS: 6474	CAS: 64742-56-9 Distillates (petroleum), solvent-dewaxedlight paraffinic					
	EC50 (21d)	>10 mg/L (Daphnia galeata)				
	EC50 (48h)	>10,000 mg/L (Daphnia galeata)				
	NOEC (21d)	10 mg/l (Daphnia galeata)				
CAS: 6892	20-66-1 Fettalkoł	nol, ethoxyliert				
	LC50 (96h)	108 mg/L (Brachydanio rerio)				
	EL50 akut (48h)	51 mg/l (Daphnia magna)				
	EL50 akut (72h)	>100 mg/l (Desmodesmus subspicatus)				
	NOEC (10d)	0.16 mg/l (Lepomis macrochirus)				
CAS: 112-	-34-5 2-(2-butoxy	vethoxy)ethanol				
Inhalative	LC50	>100 mg/L (crustacean)				
	LC50 akut (96h)	1,300 mg/L (Lepomis macrochirus)				
	LC50 akut	>100 mg/L (Brachydanio rerio)				
	EC50	>100 mg/l (Desmodesmus subspicatus)				

• 12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

\cdot 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

(Contd. of page 8)

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

· 12.7 Other adverse effects

- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

12 01 09* machining emulsions and solutions free of halogens

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	Void
 • 14.2 UN proper shipping name • ADR, IMDG, IATA 	Void
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
 · 14.7 Maritime transport in bulk according to IMO instruments · UN "Model Regulation": 	Not applicable. Void

(Contd. on page 10)

EU -



Page 10/11

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

(Contd. of page 9)

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms Void
- · Signal word Void

· Hazard statements

- H412 Harmful to aquatic life with long lasting effects.
- · Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Methanol
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

• Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases. Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.



according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 301

Revision: 18.07.2023

(Contd. of page 10)

Trade name: High-performance cooling lubricant concentrate HPC PRO E-COLL

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Contact: sdb@ede.de

· Date of previous version: 29.01.2021

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

·* Data compared to the previous version altered.

EU -